



PRODUCT DATA W/R SERIES

BIPACCO COATINGS LLC CUBA MISSOURI 573-885-2506

92 Series Eco-Tred No Slip Coating

Resin: Acrylic/Alkyd

Description: ZERO VOC Water based rubber coating. For use where slip resistance is required. Ship decks & Steps. Concrete walkways, trailers and trucks, concrete floors

Colors: Any color

Viscosity: 115-130 Ku's

VOC'S: ZERO

Flashpoint: Above 220 F

Thinner: Use clean water

Recommended Primer: 99 Series are primers to use under the 92 series topcoats when applying over bare steel

Recommended Film Thickness: 4-16 mils

Coverage: 100-200 square feet per gallon.

Solids: 55% by volume

Drying Times: @ 68 F To Touch 2 hours, recoat 8 hours, dry hard overnight. (Depending on humidity)

Products uses: An industrial coating that is user and environmentally safe. Beyond "Green" made from recycled materials.

Surface Preparation: All surface areas should be clean and dry. Remove loose paint, rust, all dirt and oil prior to painting. The surface coated over will greatly determine the smoothness of the finish.

Application: Airless Spray, Conventional Spray, Brush or Rolled. Use good quality china bristle brush or 3/8 nap roller.

The information, data, and suggestions contained herein are believed to be reliable, based on our knowledge and experience; however, it is expressly declared that the seller, manufacture, does not guarantee the result to be obtained in the buyers processes. Seller/ Manufacture expressly disclaims any implied warranty of merchantability or fitness for a particular purpose and /or any other warranty, express or implied. Buyer must make its own determination of the suitability of any product for its use. Nothing contained herein shall be construed to constitute inducement or recommendation to practice invention covered by any patent without the authority from the owner of the patent. (01/10)